

DECLARATION OF PERFORMANCE

No. BETUN 20/30

1. Name and identity code:

Bitumen for paving
BITUMEN 20/30



2. Name and address of manufacturer:

MOEVE COMMERCIAL, SAU
Pº de Castellana, nº 259 A
28046 Madrid (España)
Tel.: 91 337 60 00

<https://www.moeve.es/es/utilidades/catalogo/asfaltos/marcado-ce>

3. Applications:

Construction and maintenance of roads, aerodromes and other paved areas
(sealed against penetration)

4. System of assessment and verification of performance compliance: 2+

5. Notified body:

- AENOR 0099
- Task performed: Factory control assessment
- Assessment system: 2+
- Certificates: 0099/CPR/B11/0199 – Date issued: 30/07/2010
0099/CPR/B11/0208 – Date issued: 30/07/2010

6. Declared performance:

Essential characteristics	Performance	Harmonised technical specifications
Consistency at intermediate service temperatures		EN 12591:2009
Penetration at 25° C (en 1426)	20-30 x 0.1 mm	
Consistency at high service temperatures		
Softening point (EN 1427)	55-63° C	
Temperature dependence of consistency		
Penetration Index (EN 12591 – Annex A)	-1,5 ≤ x ≤ +0,7	
Durability – Resistance to hardening at 163°C (EN 12607-1)		
Mass change (EN 12607-1)	≤ 0,5%	
Retained penetration (EN 1426)	≥55%	
Increase in softening point (EN 1427)	≤10°C	
Brittleness at low service temperatures		
FRAASS breaking point (EN 12593)	NR	
Solubility (EN 12592)	≥99,0%	
Flash point (EN ISO 2592)	≥240°C	

- The performance of the product declared in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued at the sole responsibility of the manufacturer identified in point 2.
- Signed by and on behalf of the manufacturer by:

Gerardo Pardo Alvarez-Buylla
General Manager of Asphalts
MOEVE COMMERCIAL, SAU

Madrid, 1 de julio de 2025