

DECLARATION OF PERFORMANCE

No. **PMB 25/65-65C**

**1. Name and identity code:**

Bitumen for paving  
FLEXODUR BMC 2  
PMB 25/65-65C



**2. Name and address of manufacturer:**

MOEVE COMMERCIAL, SAU  
Pº de Castellana, nº 259 A  
28046 Madrid (España)  
Tel.: 91 337 60 00  
<https://www.moeve.es/es/utilidades/catalogo/asfaltos/marcado-ce>

**3. Applications:**

Construction and maintenance of roads, aerodromes and other paved areas  
(sealed against penetration)

**4. System of assessment and verification of performance compliance: 2+**

**5. Notified body:**

- AENOR 0099
- Task performed: Factory control assessment
- Assessment system: 2+
- Certificates: 0099/CPR/B11/0203 – Date issued: 30/07/2010

**6. Declared performance:**

Essential characteristics	Performance	Harmonised technical specifications
<b>Consistency at intermediate service temperatures</b>		EN 14023:2010
Penetration at 25°C (EN 1426)	Class 3	
<b>Consistency at high service temperatures</b>		
Softening point (EN 1427)	Class 5	
<b>Cohesion</b>		
Force-Ductility (traction at 50 mm/min) (EN 13589)	Class 11	
<b>Durability. Resistance to hardening (EN 12607-1)</b>		
Retained penetration (EN 1426)	Class 7	
Increase in softening point (EN 1427)	Class 2	
Mass change (EN 12607-1)	Class 4	
<b>Brittleness at low service temperatures</b>		
Fraass breaking point (EN 12593)	Class 4	
<b>Elastic recovery</b>		
Elastic recovery at 25°C (EN 13398)	Class 5	



- The performance of the product declared in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued at the sole responsibility of the manufacturer identified in point 2.
- Signed by and on behalf of the manufacturer by:

Gerardo Pardo Alvarez-Buylla  
General Manager of Asphalts  
MOEVE COMMERCIAL, SAU

Madrid, July 1, 2025