



DECLARATION OF PERFORMANCE

Nº. BETUN 35/50

1. **Name and identity code:**

Bitumen for paving
ASPHALT BITUMEN 35/50



2. **Name and address of manufacturer:**

Moeve Client Solutions, SAU
Pº de Castellana, nº 259 A
28046 Madrid (España)
Tel.: 91 337 60 00
<https://www.moeve.es/es/utilidades/catalogo/asfaltos/marcado-ce>

3. **Applications:**

Construction and maintenance of roads, aerodromes and other paved areas
(sealed against penetration)

4. **System of assessment and verification of performance compliance: 2+**

5. **Notified body:**

- AENOR 0099
- Task performed: Factory control assessment
- Certificates: 0099/CPR/B11/0199 – Fecha de emisión: 30/7/2010
0099/CPR/B11/0202 – Fecha de emisión: 30/7/2010
0099/CPR/B11/0203 – Fecha de emisión: 30/7/2010
0099/CPR/B11/0208 – Fecha de emisión: 30/7/2010
0099/CPR/B11/0209 – Fecha de emisión: 30/7/2010

• **Declared performance:**

Essential characteristics	Performance	Harmonised technical specifications
Consistency at intermediate service temperatures		EN 12591:2009
Penetration at 25°C (EN 1426)	35-50 x 0.1 mm	
Consistency at high service temperatures		
Softening point (EN 1427)	50-58° C	
Temperature dependence of consistency		
Penetration index (EN 12591 - Annex A)	-1,5 ≤ x ≤ + 0,7	
Durability – Resistance to hardening at 163°C (EN 12607-1)		
Mass change (EN 12607-1)	≤ 0,5%	
Retained penetration (EN 1426)	≥ 53%	
Increase in softening point (EN 1427)	≤ 11°C	
Brittleness at low service temperatures		
FRAASS breaking point (EN 12593)	≤ - 5° C	
Solubility (EN 12592)	≥ 99,0%	
Flash point (EN ISO 2592)	≥ 240°C	



- The performance of the product declared in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued at the sole responsibility of the manufacturer identified in point 2.
- Signed by and on behalf of the manufacturer by:

María González González
Head of Asphalt Technical department
Moeve Client Solutions, SAU

Madrid, June 1, 2026

FIRMADO por: MARIA GONZALEZ GONZALEZ (NIF: 50877056K)
Versión imprimible con información de firma generado desde VALIDe (<http://valide.redsara.es>)
Firma válida.